# **MSDS Summary Information**

# For further information: Please refer to the full MSDS

Issue: August 2015

PRODUCT: Nail Artistry DehydrateOther Names: Flammable Liquid NOS

**Uses:** Preparatory agent prior to nail

Enhancement application.

Pack Sizes 15ml

UN No.	1993
<b>Dangerous Goods Class</b>	3
Subsidiary Risk	None
Pack Group	II
Hazchem	3[Y]E
Poison Schedule	N/R

**Hazardous Nature:** This product is classified as hazardous under Safe Work Australia criteria

Exposure Standards: Ethyl Acetate: TWA: 720 mg/m3 (200 ppm): STEL: 500 ppm

Isopropanol: TWA 983mg/m3 (400ppm) STEL 1230mg/m3 500ppm

N Butyl Acetate: TWA 713mg/m3 (150ppm), STEL 950 mg/m3 (200ppm)

# Physical Characteristics (Typical)

Section 9 of MSDS

Appearance Clear, colourless liquid, fruity odour

Boiling Point/ Range (°C): 77
Flash Point (°C): -4

Specific Gravity/ Density (g/ml @ 15°C): 0.84 @ (20oC)

Chemical Stability: Stable under normal conditions of use

Reactivity: No decomposition products except on burning or

oxidation. See "Fire Fighting Measures" and "Hazardous

Reactions"

Product Ingredients	Section 3 of MSDS

Ethyl Acetate	141-78-6	30-60%
Isopropanol	67-63-0	30-60%
N Butyl Acetate	123-86-4	10-30%

# Risk Phrases Section 2 of MSDS

R 11 Highly Flammable R67 Vapours may cause drowsiness &

dizziness

R36 Irritating to eyes

# For further Risk and Safety information, please refer to the full MSDS.

#### **DEFINITIONS**

Dangerous Goods	Products that are classified as Dangerous for Storage and Transport: these products are allocated a UN No., with accompanying Class, Pack Group, and Sub. Risk, if required. Products that do not have a specific description under the code, but have low flash points, or such, must be classified under their most significant risk, eg. Flammable Goods N.O.S. (Not otherwise specified), UN 1993
Poisonous Substance	Products that are classified under the poisons schedule are a poisonous substance. The proportion of the poison in the product will determine its numerical classification.
Hazardous Substance	Products are considered to be Hazardous if they pose an intrinsic risk to human or environmental health, such as mutagens (able to change DNA), teratogens (able to result in birth defects), carcinogens (able to generate cell abnormalities), etc. Materials are not hazardous substances if they pose risks such as potential for misuse, like flammability, or explosions when heated and ignited.

# **Material Safety Data Sheet**

# 1. IDENTIFICATION

Product Name: Nail Artistry Dehydrate
Other Names: Flammable Liquid NOS

**Recommended Use:** Preparatory agent prior to nail enhancement application.

Supplier:The Nail ShopABN:71 365 073 683

Street Address: 22 Pleasant Grove, Holden Hill SA 5088

Telephone: 0416 157 087
Emergency Medical 13 11 26
Emergency Transport: 000

# 2. HAZARDS IDENTIFICATION

#### **Health Hazard Classification**

This product is classified as hazardous under Safe Work Australia criteria

# **Hazard Category**

Xi : Irritant

Risk Phrases

R 11 Highly Flammable R36 Irritating to eyes

R67 Vapours may cause drowsiness &

dizziness

# **Safety Phrases**

S7/9	Keep container tightly closed and in a well ventilated place.	S 16	Keep away from sources of ignition - No smoking
S 23	Do not breathe gas, fumes, vapour or spray	S 24/25	Avoid contact with skin and eyes
S 26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	S 29	Do not empty into drains
S 33	Take precautionary measures against static discharges	S43B	In case of fire use sand, earth, chemical powder or alcohol type foam

# **Dangerous Goods Classification**

3

#### **Poisons Schedule**

N/R

COMPOSITION: Information on Ingredients

-78-6 30-60
63-0 30-60
-86-4 10-30

Date of Issue: August 2015 Page 2 of 7

# 3. FIRST AID MEASURES

# For advice, contact Poisons Information Centre (Phone Australia: 13 1126) or a doctor.

# **Ingestion**

If swallowed, DO NOT induce vomiting. Keep at rest. Seek immediate medical attention.

# **Eye Contact**

Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.

# **Skin Contact**

Flush area with large amounts of water and wash area with soap if available. Remove contaminated clothing, including shoes, and launder before reuse. Seek medical attention for skin irritations.

#### Inhalation

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Seek immediate medical attention.

# **First Aid facilities**

Provide eye baths and safety showers.

# **Medical Attention**

Treat according to symptoms. Avoid gastric lavage: risk of aspiration of product to the lungs with the potential to cause chemical pneumonitis.

# 4. FIRE FIGHTING MEASURES

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing firefighters with this Material Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

# Suitable extinguishing media

Dry chemical or foam

# Hazards from combustion products

Carbon monoxide and carbon dioxide

# Precautions for fire fighters and special protective equipment

Full protective clothing and self-contained breathing apparatus

# **Hazchem Code:**

3[Y]E

# 5. ACCIDENTAL RELEASE MEASURES

# **Emergency Procedures**

Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum. Prevent vapours from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.

# Methods and materials for containment

# **Major Land Spill**

- Eliminate sources of ignition.
- Warn occupants of downwind areas of possible fire and explosion hazard.
- Prevent liquid from entering sewers, watercourses, or low-lying areas.
- Keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.

Date of Issue: August 2015 Page 3 of 7

# **Material Safety Data Sheet**

- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.
- Take measures to minimise the effect on the ground water.
- Contain the spilled liquid with sand or earth.
- Recover by pumping use explosion proof pump or hand pump or with a suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity"

# 6. HANDLING AND STORAGE

# **Precautions for safe handling**

This product is flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Material will accumulate static charge. Use grounding leads to avoid discharge (electrical spark).

# **Conditions for safe storage**

Store in a cool, dry place away from direct sunlight. Do not pressurise, cut, heat or weld containers - residual vapours are flammable. This product is flammable and will fuel a fire in progress.

# **Incompatible materials**

Natural rubbers, polystyrene, vinyl plastics, EDPM

# 7. EXPOSURE CONTROLS: PERSONAL PROTECTION

# **National Exposure Standards**

Ethyl Acetate: TWA 720mg/m3 (200ppm), STEL 500ppm Isopropanol: TWA 983mg/m3 (400ppm), STEL 500ppm N Butyl Acetate: TWA 713mg/m3 (150ppm), STEL 200ppm

Where the TWA is the highest allowable exposure concentration in a 8 hour day for a five day working week. STEL is the maximum allowable exposure concentration at any time.

# **Biological limit values**

Not available

# **Engineering Controls: Ventilation**

The use of local exhaust ventilation is recommended to control process emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

# **Personal Protective Equipment**

**Respiratory Protection:** Where concentrations in air may exceed the limits described in the National Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product.

Eye Protection: Always use safety glasses or a face shield when handling this product.

**Skin/ Body Protection:** Always wear long sleeves and long trousers or coveralls, and enclosed footwear or safety boots when handling this product

Date of Issue: August 2015 Page 4 of 7

# PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear, colourless liquid with fruity
		odour
Boiling Point/ Range	°C	77
Flash Point	°C	-4
Density @ 15°C	g/ml	0.84 @ (20oC)
Vapour Pressure @ 20°C	kPa	Not available
Explosive Limits (LEL – UEL)	%	1.7 – 12.0
Vapour Density @ 20°C	kPa	Not available
Autoignition Temperature	°C	>350
Viscosity @ 20°C	cSt	Not applicable
Percent Volatiles	%	100%
Solubility with Water	% w/w	50%

The values listed are indicative of this product's physical and chemical properties. For a full product specification, please consult the Product Data Sheet.

# 8. STABILITY AND REACTIVITY

# **Chemical Stability**

Stable under normal conditions of use

# **Conditions to avoid**

Sources of heat and ignition, open flames.

# **Hazardous decomposition products**

No decomposition products except on burning or oxidation. See "Fire Fighting Measures" and "Hazardous Reactions"

#### **Hazardous reactions**

Strong oxidising agents such as hydrogen peroxide, nitric acid, perchloric acid, chromium trioxide. Metal acids, alkalis and heat.

# 9. TOXICOLOGICAL INFORMATION

# **Acute Effects**

#### Ingestion

Swallowing can result in nausea, vomiting, shortness of breath, headache, drowsiness, and dizziness, loss of consciousness and possible death. Respiratory and CNS depression may occur. Aspiration of ingested product into the lungs may cause chemical pneumonitis.

# Eye Contact

Vapour and liquid are eye irritants. Symptoms include redness, swelling and temporary corneal damage. Corneal burns are possible with this product.

#### Skin Contact

Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Date of Issue: August 2015 Page 5 of 7

#### Inhalation

Vapour may be irritating to the mucose membranes and respiratory tract. Inhalation of high concentrations can produce central nervous system depression including impaired judgement, loss of coordination, dizziness, nausea, and if exposure is prolonged, loss of consciousness

# **Chronic Effects**

Absorption via the skin can produce narcotic effects. People with pre existing disease of the liver and/or kidneys should avoid unnecessary exposure to the product. Long term skin contact may product defatting of the skin and irritant contact dermatitis.

# **Other Health Effects Information**

Symptoms of exposure include cough, shortness of breath and dizziness. Questionable carcinogen. Mutation data reported. Experimental teratogenic and reproductive effects reported.

# **Toxicological Information**

LD50 Ethyl Acetate: 5620mg/kg oral, rat

Isopropanol: 5045 mg/kg oral, rat N Butyl Acetate: 10,768 mg/kg oral, rat

LC50 Ethyl Acetate: 1,600 ppm/8 hrs, rat

Isopropanol: 4,650 ppm/4hrs, rat N Butyl Acetate: 390 ppm/4hrs, rat

TCLo Ethyl Acetate : 400ppm, human

N Butyl Acetate: 200ppm, human

# 10. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

# **Aquatic Toxicity**

No data available, but based upon data for similar preparations and components this product is expected to be toxic to aquatic organisms.

# Persistence/ degradability

This product can degrade rapidly in air. This substance is expected to be removed in wastewater treatment. Based upon data for a similar components or estimated data, this product is expected to biodegrade rapidly and be 'readily' biodegradable according to OECD guidelines.

# **Mobility**

Product is highly volatile, but may contaminate groundwater upon entering soil.

# 11. DISPOSAL CONSIDERATIONS

# **Disposal Methods**

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry.

# **Special Precautions for Landfill or Incineration**

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

Date of Issue: August 2015 Page 6 of 7

# 12. TRANSPORT INFORMATION

Road and R	I Rail Transport Marine Transport		Air Tı	r Transport	
UN No.	1993	UN No.	1993	UN No.	1993
Proper Shipping Name	Flammable Liquid NOS	Proper Shipping Name	Flammable Liquid NOS	Proper Shipping Name	Flammable Liquid NOS
DG Class	3	DG Class	3	DG Class	3
Sub. Risk	None	Sub. Risk	None	Sub. Risk	None
Pack Group	II	Pack Group	11	Pack Group	II
Hazchem	3[Y]E				

# **Dangerous Goods Segregation**

This product is classed as Dangerous Goods Class 3, packing group II. Please consult the Australian Dangerous Goods Code for Transport by Road and Rail for information.

# 13. REGULATORY INFORMATION

Country/ Region: Australia

Inventory: AICS Status: Listed

Poisons Schedule: N/R

# 14. OTHER INFORMATION

#### Abbreviations:

AICS: Australian Inventory of Chemical Substances

CAS Number: Chemical Abstracts Number

IARC: International Agency for Research on Cancer

NOHSC: National Occupational Health and Safety Council

## References:

Supplier Material Safety Data Sheets

• Sax's Dangerous Properties of Industrial Materials, Richard J. Lewis Snr., pub. Canada (2000)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product.

Date of Issue: August 2015 Date of Review: January 217