THE NAIL SHOP SQUEAKY CLEAN NAIL SOLUTION

RMATION ONLY The Nail Shop Squeaky Tammable Liquid NOS Acetone, n Butyl Acetate		Issue: Augus UN No.			
lammable Liquid NOS		UN No.			
	(leanrananal		1993		
cetone, n Butyl Acetate	(isopropanoi,	Dangerous Goods Class	3		
	e)	Subsidiary Risk	None		
lail plate cleansing prio	or to artificial nail	Pack Group	II		
nhancements		Hazchem	2[Y]E		
		Poison Schedule	N/R		
e: This product is	classified as haza	ardous under SafeWork Australia crite	eria		
rds: Isopropanol, TV	VA: 983 mg/m3 (4	100 ppm): STEL: 1230 mg/m3 (500 p	pm)		
Acetone, TWA	: 1185mgm3 (500	oppm), STEL 2375 mg/m3 (1000ppm))		
N Butyl Acetate	e , TWA : 713mg/r	n3 (150ppm), STEL 950mg/m3 (200p	opm)		
eristics (Typical)		Section 9 of MSDS			
	Blue tinted liqu	id with fruity fragrance			
ge (°C):	Begins at 56				
	-17				
ensity (g/ml @ 15°C):	0.795				
Chemical Stability: Stable under normal conditions of use					
			; "Fire		
nts		Section 3 of MSDS			
67-63-0	0	60-90%			
67-64-	1	10-30%			
123-86	5-4	10-30%			
gredients		1%			
For further ingredients	information, pleas	se refer to the full MSDS.			
ating to eyes	R 67	Vapours may cause drowsiness dizziness	and		
hly flammable	R66		skin		
or further Risk and Safe	ety information, plo	, ,			
DEFINITIONS					
accompanying Class, Pack Gro code, but have low flash points	oup, and Sub. Risk, if requ , or such, must be classifi	ired. Products that do not have a specific description u	under the		
		are a poisonous substance. The proportion of the poiso	on in the		
Hazardous Substance Products are considered to be Hazardous if they pose an intrinsic risk to human or environmental health, such as mutagens (able to change DNA), teratogens (able to result in birth defects), carcinogens (able to generate cell abnormalities), etc. Materials are not hazardous substances if they pose risks such as potential for misuse, like					
	rds: Isopropanol, TV Acetone , TWA N Butyl Acetate eristics (Typical) ge (°C): pensity (g/ml @ 15°C): nts 67-63-0 67-64- 123-86 gredients For further ingredients For further ingredients for further specified, UN ating to eyes hly flammable or further Risk and Safe Products that are classified as accompanying Class, Pack Gro code, but have low flash points (Not otherwise specified), UN Products that are classified as accompanying Class, Pack Gro code, but have low flash points (Not otherwise specified), UN Products that are classified un product will determine its nume Products are considered to be mutagens (able to change DN/ abnormalities), etc. Materials a	rds: Isopropanol, TWA: 983 mg/m3 (4 Acetone , TWA: 1185mgm3 (500 N Butyl Acetate , TWA : 713mg/r eristics (Typical) Blue tinted liqu ge (°C): Begins at 56 -17 Density (g/ml @ 15°C): 0.795 Stable under n No decomposit Fighting Measu 67-63-0 67-64-1 123-86-4 gredients For further ingredients information, pleas ating to eyes R 67 hly flammable R66 or further Risk and Safety information, pleas Products that are classified as Dangerous for Storage an accompanying Class, Pack Group, and Sub. Risk, if requ code, but have low flash points, or such, must be classifi (Not otherwise specified), UN 1993 Products that are classified under the poisons schedule a products will determine its numerical classification. Products are considered to be Hazardous if they pose ar mutagens (able to change DNA), teratogens (able to ress	e: This product is classified as hazardous under SafeWork Australia crite rds: Isopropanol, TWA: 983 mg/m3 (400 ppm): STEL: 1230 mg/m3 (500 p Acetone , TWA: 1185mgm3 (500ppm), STEL 2375 mg/m3 (1000ppm) N Butyl Acetate , TWA : 713mg/m3 (150ppm), STEL 950mg/m3 (200p eristics (Typical) Section 9 of MSDS Blue tinted liquid with fruity fragrance ge (°C): Begins at 56 -17 bensity (g/ml @ 15°C): 0.795 Stable under normal conditions of use No decomposition products except on burning. See Fighting Measures". nts Section 3 of MSDS 67-63-0 60-90% 67-64-1 10-30% 123-86-4 10-30% gredients 1% For further ingredients information, please refer to the full MSDS. Section 2 of MSDS ating to eyes R 67 Vapours may cause drowsiness dizziness hly flammable R66 Repeated exposure may cause dryness or cracking or further Risk and Safety information, please refer to the full MSDS. Products that are classified as Dangerous for Storage and Transport: these products are allocated a UN No., wi accompanying Class, Pack Group, and Sub. Risk, if required. Products that do not have a specific description or dott will determine its numerical classified under their most significant risk, eg. Flammable Goo (Not otherwise specified). UN 1993 Products that are classified as Dangerous for Storage and Transport: these products are allocated a UN No., wi accompanying Class, Pack Group, and Sub. Risk, if required. Products that do not have a specific description u code, but have low flash points, or such, must be classified under their most significant risk, eg. Flammable Goo (Not otherwise specified). UN 1993 Products that are classified under the poisons substance. The proportion of the poison product will determine its numerical classified to result in birth defects), carcinogens (able to generate cell antormatives, etc. Materia era on tharadous si they pose an intrinsic risk to human or environmental health, such a mutagens (able to change DNA), teratogens (able to result in birth defects), carcinogens (able to gene		

SUMMARY INFORMATION ONLY

THE NAIL SHOP SQUEAKY CLEAN NAIL SOLUTION

MSDS

1. IDENTIFICATION

Product Name:	The Nail Shop Squeaky Clean Nail Solution		
Other Names:	Flammable Liquid NOS (Isopropanol, Acetone, n Butyl Acetate)		
Chemical Family:	Solvent hydrocarbons		
Molecular formula:			
Recommended Use:	Nail plate cleansing prior to nail enhancements.		
Supplier:	The Nail Shop		
ABN:	71 365 073 683		
Street Address:	22 Pleasant Grove, Holden Hill SA 5088		
Telephone:	0416157087		

2. HAZARDS IDENTIFICATION

Health Hazard Classification

This product is classified as hazardous under SafeWork Australia criteria

Hazard Category

Xi: Irritant

Risk Phrases

NISK I III US			
R 36	Irritating to eyes	R 67	Vapours may cause drowsiness and dizziness
R 11	Highly flammable	R66	Repeated exposure may cause skin dryness or cracking
Safety Phra	ases		
S2	Keep out of reach of children		
S 7/9	Keep container tightly closed and in a well ventilated place	S 16	Keep away from sources of ignition - No smoking
S 24/25	Avoid contact with skin and eyes	S 26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S 33	Take precautionary measures against static discharges	S 43B	In case of fire use sand, earth, chemical powder or alcohol type foam
Dangerous	Goods Classification		
3 PGII			

3 PGII

Poisons Schedule

N/R

3. COMPOSITION: Information on Ingredients

Chemical Ingredient	CAS No.	Proportion (%v/v)
Isopropyl Alcohol	67-63-0	60-90%
Acetone	67-64-1	10-30%
N Butyl Acetate	123-86-4	10-30%
Non Hazardous ingredients		1%

4. FIRST AID MEASURES

For advice, contact Poisons Information Centre (Phone Australia: 13 1126) or a doctor.

Ingestion

If swallowed, DO NOT induce vomiting. If patient is conscious rinse mouth with water. Keep at rest. Seek immediate medical attention.

Eye Contact

Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.

Skin Contact

Flush area with large amounts of water and wash area with soap if available. Remove contaminated clothing, including shoes, and launder before reuse. Seek medical attention for skin irritations.

Inhalation

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Seek immediate medical attention.

First Aid facilities

Provide eye baths and safety showers.

Medical Attention

Treat according to symptoms. Avoid gastric lavage: risk of aspiration of product to the lungs with the potential to cause chemical pneumonitis.

5. FIRE FIGHTING MEASURES

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing firefighters with this Material Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

Suitable extinguishing media

Water spray, water fog or fine mist, alcohol foam

Hazards from combustion products

Carbon dioxide and carbon monoxide

Precautions for fire fighters and special protective equipment

Full protective clothing and self-contained breathing apparatus

Hazchem Code:

3[Y]E

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum. Prevent vapours from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.

Methods and materials for containment

Major Land Spill

- Eliminate sources of ignition.
- Warn occupants of downwind areas of possible fire and explosion hazard.
- Prevent liquid from entering sewers, watercourses, or low-lying areas.
- Keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.

THE NAIL SHOP SQUEAKY CLEAN NAIL SOLUTION

- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.
- Take measures to minimise the effect on the ground water.
- Contain the spilled liquid with sand or earth.
- Recover by pumping use explosion proof pump or hand pump or with a suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity"

Major Water Spill

- Eliminate any sources of ignition.
- Warn occupants and shipping in downwind areas of possible fire and explosion hazard.
- Notify the port or relevant authority and keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.
- Confine the spill if possible.
- Remove the product from the surface by skimming or with suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity".

7. HANDLING AND STORAGE

Precautions for safe handling

This product is flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Use grounding leads to avoid discharge (electrical spark).

Conditions for safe storage

Store in a cool, dry place away from direct sunlight. Do not pressurise, cut, heat or weld containers - residual vapours are flammable. This product is flammable and will fuel a fire in progress.

Incompatible materials

Natural Rubber, Butyl Rubber, EPDM, Polystyrene

8. EXPOSURE CONTROLS: PERSONAL PROTECTION

National Exposure Standards

Isopropanol, TWA: 983 mg/m3 (400 ppm): STEL: 1230 mg/m3 (500 ppm)

Acetone , TWA: 1185mgm3 (500ppm), STEL 2375 mg/m3 (1000ppm)

N Butyl Acetate, TWA: 713mg/m3 (150ppm), STEL 950mg/m3 (200ppm)

Engineering Controls: Ventilation

The use of local exhaust ventilation is recommended to control process emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

Personal Protective Equipment

Respiratory Protection: Where concentrations in air may exceed the limits described in the National Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product.

Eye Protection: Always use safety glasses or a face shield when handling this product.

Skin/ Body Protection: Always wear long sleeves and long trousers or coveralls, and enclosed footwear or safety boots when handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Blue tinted fruity liquid
Boiling Point/ Range	°C	Begins at 56
Flash Point	°C	-17
Density @ 15°C	g/ml	0.795
Vapour Pressure @ 20°C	kPa	4.3
Explosive Limits (LEL – UEL)	%	1.8 – 12.0
Vapour Density @ 20°C	kPa	> 1.00
Autoignition Temperature	°C	> 350
Viscosity @ 20°C	cSt	Not applicable
Percent Volatiles	%	99%
Solubility with Water	% w/w	100%

The values listed are indicative of this product's physical and chemical properties. For a full product specification, please consult the Product Data Sheet.

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of use

Conditions to avoid

Sources of heat and ignition, open flames.

Hazardous decomposition products

No decomposition products except on burning. See "Fire Fighting Measures".

Hazardous reactions

Stored mixtures with MEK produce explosive peroxides. Increased rate of peroxide formation with Isobutanol. Peroxide production sharply decreases the Autoignition Temperature. Violent, explosive reactions with metal oxides, oxidising agents, halogenated organic compounds and mineral acids.

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion

The single lethal dose for humans is approx. 250ml, however 100ml can be fatal. Symptoms of overexposure include: flushing, pulse rate decrease, blood pressure lowering, anaesthesia, narcosis, headaches, dizziness, mental depression, hallucinations, distorted perceptions, respiratory depression, nausea or vomiting, coma. Vomiting may cause the product to be aspirated to the lungs resulting in chemical pneumonitis.

Eye Contact

This product is irritating to eyes and can cause corneal burns.

Skin Contact

This product is irritating to the skin with prolonged exposure. It may result in dryness and cracking.

Inhalation

This product is irritating to the respiratory tract. In high doses, this product has narcotic effects. At concentrations of 400ppm or higher, the product may induce a mild narcosis, with transient effects. See Ingestion Effects.

Chronic Effects

A slight tolerance to this product can be acquired. This product is easily absorbed by the skin yielding a narcotic action. Overexposure may not be immediately determined for those who have built a tolerance. Abuse of this product will be harmful. People with pre-existing liver or kidney conditions must avoid unnecessary product exposure (metabolises similarly to ethanols).

Other Health Effects Information

Questionable carcinogen. Mutation data reported. Experimental teratogenic and reproductive effects.

Toxicological Information

2-propanol: 5045 mg/kg (oral, rat) TDLo: 223 mg/kg (oral, human) Acetone : 5800-8400 mg/kg (oral, rat), 20g/kg (dermal rabbit), LC50 32000ppm for 4 hours (rat) N Butyl Acetate: 320mg/kg (oral LD50 rabbit), 1200mg/kg (oral LD50 Mouse)

12. ECOLOGICAL INFORMATION

Ecotoxicity

Aquatic Toxicity

Fish Toxicity (rainbow trout, goldfish, bluegill):	LC_{50} (96hr): Based on data for a similar component or preparation, this product is expected to be toxic to aquatic organisms.
Daphnia Magna EC ₅₀ (24 hr):	No data available
Daphnia Magna EC ₅₀ (48 hr):	Long term adverse effects to aquatic organisms are possible if continuous exposure is maintained.
Blue-green algae (Toxicity threshold 7-8 days):	No data available
Green algae (Toxicity threshold 7-8 days):	No data available

Persistence/ degradability

This product can degrade rapidly in air. This substance is expected to be removed in wastewater treatment. Based upon data for a similar components or estimated data, this product is expected to biodegrade rapidly and be 'readily' biodegradable according to OECD guidelines.

Mobility

This product is highly volatile and will rapidly evaporate to the air if released into the water

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry.

Special Precautions for Landfill or Incineration

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

14. TRANSPORT INFORMATION

Road and Rail Transport		Marine Transport		Air Transport	
UN No.	1993	UN No.	1993	UN No.	1993
Proper Shipping Name	Flammable Liquid NOS(Isopropyl Alcohol, Acetone, n Butyl Acetate)	Proper Shipping Name	Flammable Liquid NOS(Isopropyl Alcohol, Acetone, n Butyl Acetate)	Proper Shipping Name	Flammable Liquid NOS(Isopropyl Alcohol, Acetone, n Butyl Acetate)
DG Class	3	DG Class	3	DG Class	3
Sub. Risk	None	Sub. Risk	None	Sub. Risk	None
Pack Group	II	Pack Group	II	Pack Group	II
Hazchem	3[Y]E				

Dangerous Goods Segregation

This product is classed as Dangerous Goods Class 3, packing group II. Please consult the Australian Dangerous Goods Code for Transport by Road and Rail for information.

15. REGULATORY INFORMATION

Country/ Region: Australia Inventory: AICS Status: Listed Poisons Schedule: N/R

16. OTHER INFORMATION

Date of creation : August 2014. Revision date :January 2017 Abbreviations:

AICS: Australian Inventory of Chemical Substances CAS Number: Chemical Abstracts Number IARC: International Agency for Research on Cancer NOHSC: National Occupational Health and Safety Council

References:

- Supplier Material Safety Data Sheets
- Sax's Dangerous Properties of Industrial Materials, Richard J. Lewis Snr., pub. Canada (2000)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact The Nail Shop.